

SPOT SERIES • ME12S

Compact, ultra-high performance passive trapezoidal cabinet

- Custom components.
- Superlative weight/power ratio (19 kg / 128 dB peak at 1 metre).
- Passive cabinet with 1 x 12" and 1" driver.
- 90° x 40° rotatable diffuser.
- Passive filter with high phase coherence; crafted with premium electronic components.
- HEPC® (High-End Phase Coherence) filter technology.
- Ideal for portable PA systems (combined with our SUB Series subwoofers) and permanent installations.
- 8 rigging points per M8 nut.
- Socket for standard tripod with two mounting positions at 0° and 5°.
- Made with 18-ply Finnish birch wood.
- Finished with a special waterproof polyurea coating resistant to erosion and degradation.
- Robust construction in panels assembled with tongue-and-groove techniques and subsequently glued and pressed.
- Front grid with hexagonal punching and high-resistance epoxy finish.
- Special acoustic foam coating for protection of the loudspeakers against dust and dirt.
- Maga Engineering® limited 5-year warranty.





TECHNICAL SPECIFICATIONS

Frequency response:	45 Hz – 19 KHz (+/- 3 dB)
Sensitivity (1 W at 1 metre):	97 dB
Admissible power (continuous):	600 W AES
Recommended amplification:	500 W to 1000 W
Rated impedance:	8 Ω
Maximum SPL:	128 dB peak at 1 metre
Diffuser:	90° x 40°, rotatable
Bass components:	1 x 12" ferrite, 500 W AES, 8 Ω
Treble components:	1" ferrite, 40 W AES, 8 Ω

CABINET DIMENSIONS (VERTICAL POSITION)

Front:	368 x 621 mm
Rear:	300 mm
Net weight:	19 kg
Connections:	2 x Neutrik® speakON®



DIMENSIONS

