

WEDGE SERIES • ME12WX

Multi-purpose passive stage monitor

- Custom components.
- Passive stage monitor with 1 x 12" + 1 x 2.84" coaxial driver.
- Passive filter with high phase coherence; crafted with premium electronic components.
- HEPC® (High-End Phase Coherence) filter technology.
- PA/monitor position.
- Excellent performance as monitor.
- Low feedback.
- Light weight (21.3 kg).
- Socket for standard tripod with two mounting positions at 0° and 5°.
- Made with 18-ply Finnish birch wood.
- Finished with a special waterproof polyurea coating resistant to erosion and degradation.
- Robust construction in panels assembled with tongue-and-groove techniques and subsequently glued and pressed.
- Front grid with hexagonal punching and high-resistance epoxy finish.
- Special acoustic foam coating for protection of the loudspeakers against dust and dirt.
- Maga Engineering® limited 5-year warranty.



Armonía+Plus
System Manager





TECHNICAL SPECIFICATIONS

Frequency response:	52 Hz – 20 KHz (+/- 3 dB)
Sensitivity (1 W at 1 metre):	96 dB
Maximum SPL:	128 dB peak at 1 metre
Diffuser:	60°, conical
Recommended amplification:	600 W to 1000 W
Bass components:	1 x 12" ferrite, 500 W AES, 8 Ω
Treble components:	1 x 2.84" neodymium, 90 W AES, 16 Ω

CABINET DIMENSIONS

Front:	444 x 390 mm
Rear:	321.67 mm
Net weight:	21.3 kg
Connections:	2 x Neutrik® speakON®



DIMENSIONS

